

# RP-PLUS DEW 41

RUST PREVENTATIVES

325201501



## DEWATERING RUST PREVENTION FLUID

This is a light fluid product that contains solvents, corrosion inhibitors, and hydrofugant additives to provide water repellence and displacing properties. It leaves a light amber, oil-waxy film with exceptional anti-rust properties. The film lasts for up to 6 months outdoors and up to 18 months indoors, leaving a greasy-oily residue. The primary purpose of this product is to safeguard ferrous and non-ferrous industrial components and transportation parts during covered shipment and storage, whether indoors or outdoors. It can also be used to protect parts that have been machined with metalworking emulsions or machinery that has come into contact with water. Furthermore, it is a suitable final layer of protection for sheet steel and tubes.

## CATEGORY

Rust Preventatives

## BENEFITS

| PROPERTY                            | METHOD | VALUE                |
|-------------------------------------|--------|----------------------|
| Appearance                          |        | Liquid with solvents |
| Colour                              |        | Amber                |
| Density @ 20 °C, kg/dm <sup>3</sup> |        | 0.89                 |
| Type of film                        |        | Waxy-oily            |
| Drying time, minutes                |        | 30                   |
| Flash point, °C                     |        | 50                   |
| Salt spray test chamber, hours      |        | 72                   |
| Outdoor protection (months)         |        | 6                    |
| Indoor protection (months)          |        | 18                   |

All data on this technical data sheet is indicative only

202312V01



DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM

DYADE MAINTAIN THE THINGS WE VALUE