

# RP-PLUS OB 78

RUST PREVENTATIVES

325201601



## OIL BASED RUST PREVENTATIVE

The thin oily film formed by this oil-based rust preventive offers durable protection to both ferrous and non-ferrous metals, making it an exceptional product for preventing rust. The product was designed for use in scenarios that call for protection during indoor storage for durations ranging from six to twelve months, as well as for outdoor storage for up to six months. Some common applications include: Safeguarding completed machine components before they are packaged Providing inter-operative protection for machined or ground metal surfaces, such as valves, rollers, and fasteners Shielding parts during storage when a minimum film thickness is necessary.

## CATEGORY

■ Rust Preventatives

## BENEFITS

PROPERTY	METHOD	VALUE
Appearance		Light Brown
Density @ 20 °C, kg/dm <sup>3</sup>		0.86
Viscosity @ 40 °C, mm <sup>2</sup> /s		7.2
Film type		Oily
Flash point C.O.C, °C		65
Indoor protection (months)		6-12
Outdoor protection (months)		6

All data on this technical data sheet is indicative only

202312V01



DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM

DYADE MAINTAIN THE THINGS WE VALUE