

RP-PLUS DEW 24

RUST PREVENTATIVES

325202601

DYADE
LUBRICANTS



DEWATERING RUST PREVENTION FLUID

The product is a water-soluble oil that contains corrosion inhibitors, and when it evaporates, it leaves an oily film on the components. Essentially, this product provides temporary protection between machining stages for a period of 2 to 5 days, when used indoors. The level of protection can vary from a few days to 4 or 6 weeks, depending on the concentration used.

CATEGORY

- Rust Preventatives

BENEFITS

- Temporal protection between machining stages
- Economical use
- Easy to apply

PROPERTY	METHOD	VALUE
Aspect		Oily liquid
Colour		Amber transparent
Density @ 20 °C, kg/dm ³		0.91
Flash point C.O.C, °C		160
Pour point, °C		-5
Stability		good
Emulsion Colour @ 20% in water		Milky
pH emulsion @ 20% in water		9.1 ± 0.2

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM