

# MWF-PLUS NT BIO SCO

NEAT/PURE METALWORKING FLUIDS

325403101

**DYADE**  
LUBRICANTS



## MQL SPRAYING CUTTING OIL

The synthetic oil offered is a highly stable and chemically resistant lubricant that provides excellent oxidation resistance. It is ideal for use in milling and sawing operations, as it is chlorine-free and readily biodegradable. This lubricant will leave a thin film and is not completely evaporable. The product can be effectively sprayed in Minimum Quantity Lubrication systems during sawing, milling, and drilling operations on all types of metal. Additionally, it can serve as a conventional cutting oil in machining operations and as a lubricant in forming operations such as stamping and drawing.

## CATEGORY

- Metalworking Fluids

## BENEFITS

- Good flushing, cooling and lubricating properties
- Improved tool life and surface finish
- Less waste oil in chips
- Improved productivity
- Biodegradability

PROPERTY	METHOD	VALUE
Appearance		Oily liquid
Colour		Clear yellow
Density @ 20 °C, kg/dm <sup>3</sup>		0,91
Viscosity @ 40 °C, mm <sup>2</sup> /s		33
Flash point, °C		210
Pour point, °C		-8

All data on this technical data sheet is indicative only

202312V01



**DYADE** MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM