

MWF-PLUS NT FROM ST-FO 53

NEAT/PURE METALWORKING FLUIDS

325404001



STAMPING AND FORMING OIL

This low viscosity evaporating oil is formulated specifically for stamping and forming applications, with polar compounds that ensure optimal performance. Its primary advantage is that parts do not require degreasing due to the low residue left behind after use. This product is appropriate for conventional cutting, forming, and fine blanking of aluminium, steel, and copper, as well as for use in automotive parts. It can be applied directly using a brush, cloth, or other similar methods

CATEGORY

- Metalworking Fluids

BENEFITS

- Avoids contact piece and die
- Easy to apply
- Less defect in pieces
- Minimum wear in tools
- High film strength
- Better piece finishing

PROPERTY	METHOD	VALUE
Appearance		Colourless liquid
Density @ 20 °C, kg/dm ³		0.76
Viscosity @ 40 °C, mm ² /s		1.7
Flash point C.O.C, °C		>72
Pour point, °C		<-40

All data on this technical data sheet is indicative only

202312V01



DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM

DYADE MAINTAIN THE THINGS WE VALUE