

# MWF-PLUS NT FROM 28

NEAT/PURE METALWORKING FLUIDS

325406501



## FORMING LUBRICANT

This is a water-miscible product specifically designed for forming operations, containing E.P. additives to enhance lubrication. It is ideal for hot extrusion of copper and brass at a recommended dilution rate of 10-20%. Additionally, it can be used for cold forming operations like drawing and stamping of steels and stainless steel, either pure or at a 10-30% dilution rate. Mixing the product is effortless, just add it to water and mix the concentrate to the desired dilution.

## CATEGORY

- Metalworking Fluids

## BENEFITS

- Improves lifetime of dies
- Good finishing result
- High tackiness
- Excellent EP properties

PROPERTY	METHOD	VALUE
Aspect		Oily
Density @ 20 °C, kg/dm <sup>3</sup>		0.96
Emulsion		Milky stable
pH emulsion @ 5%		9.1
Stability		good

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM