

MWF-PLUS NT QW STL 67

NEAT/PURE METALWORKING FLUIDS

325407801



STEEL QUENCHING OIL

This product is a heat treatment quenching oil suitable for all types of steels heated using salts, electrical furnaces, or liquid fuels. It is a highly refined oil with excellent oxidation resistance and minimal deposit formation.

CATEGORY

- Metalworking Fluids

BENEFITS

- High quenching properties
- Superior thermal stability
- Low surface tension
- Low aromatics
- Minimum residues
- Steady quenching capacity

PROPERTY	METHOD	VALUE
Viscosity @ 40 °C, mm ² /s		27-32
Density @ 20 °C, kg/dm ³		0.87
Flash point C.O.C, °C		200
Pour point, °C		-10
TAN, mg KOH/g		0.1
Cooling rate @ 300 °C/s		51
Conradson residue, %		<0.5
Specific heat @ 30-60 °C, kCal/kg °C		0.45

All data on this technical data sheet is indicative only

202312V01



DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM

DYADE MAINTAIN THE THINGS WE VALUE