

MWF-PLUS NT CO GR-92

NEAT/PURE METALWORKING FLUIDS

325408501



LOW MIST GRINDING AND MACHINING NEAT CUTTING OIL

Formulated from hydrotreated paraffinic oil, this cutting oil contains balanced additives that maximize performance across a wide range of pressures and temperatures encountered in challenging machining conditions. It has a low evaporation rate and produces minimal mist, resulting in lower consumption. The product's lubricating properties are essential in reducing the loads imparted to the cutting edge during tough material cutting. Additionally, it does not contain chlorine or heavy metals. This product is suitable for grinding and machining applications that require a high-quality surface finish. It can be used with both ferrous and non-ferrous metals, including steel, bronze, copper, and aluminum.

CATEGORY

- Metalworking Fluids

BENEFITS

- Good Flushing, cooling and lubricating properties
- Low volatility/low mist/lower consumption
- Improved tool life and surface finish
- Improved productivity

PROPERTY	METHOD	VALUE
Colour		Clear Yellow
Viscosity @ 40 °C, mm ² /s		12-14 cSt
Flash point C.O.C, °C		185
Pour point, °C		-25
Aniline point, °C		120
FOUT		0.84
Colour		Clear Yellow
Viscosity @ 40 °C, mm ² /s		12-14 cSt
Flash point C.O.C, °C		185
Pour point, °C		-25
Aniline point, °C		120
FOUT		0.84

All data on this technical data sheet is indicative only

202312V01



DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM

DYADE MAINTAIN THE THINGS WE VALUE