ANUBIAS 4T FCW SAE 10W/30

4-STROKE OUTBOARD ENGINE OIL





4-STROKE OUTBOARD ENGINE OIL

This is a high quality semi-synthetic in/outboard motor oil that is specifically developed for marine applications that need the NMMA FC-W specification (e.g. Mercury Marine, Yamaha). This product has a very good oxidation and corrosion protection and ensures long equipment lifetime. This product can be used in "sterndrive & inboard" applications. It is also applicable for the more traditional 4-stroke outboard engines. These products are also very well suitable for salt water marine applications.

FUEL ECONOMY RATING



SPECIFICATIONS

API SJ	NMMA FC-W
API SL	

GRADE	METHOD	UNIT	VALUE	
Density	ASTM D4052	kg/l	0,874	
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	73,3	
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	11,4	
Viscosity Index	ASTM D2270		148	
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	7	
Pour point	ASTM D6892	°C		
Flash point	ASTM D92	°C	220	
Sulphated ash content	ASTM D874	%		



Product information

People buy this product because they need an excellent 10W/30 NMMA FC-W marine engine oil.

CATEGORY

- Outboard
- Engine Oil

BASE OIL

Semi-Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

