

ANUBIAS 2T - TWC3 SS

2-STROKE OUTBOARD ENGINE OIL

325600401



2-STROKE OUTBOARD ENGINE OIL

This is a semi-synthetic outboard engine oil suitable for water-cooled 2-stroke outboard engines meeting NMMA TC-W3 specifications. The semi-synthetic composition of this oil ensures that the engine lifetime is extended tremendously. The ash less components in this prevents the formation of deposits, pre-ignition and spark plug fouling. This product can be used for 2-stroke gasoline engines with high power like; outboard motors, jet skis and personal watercraft.

FUEL ECONOMY RATING



SPECIFICATIONS

API TC NMMA TC-W3
JASO FC

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,859
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	42,7
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	7,8
Viscosity Index	ASTM D2270		155
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	5,2
Pour point	ASTM D6892	°C	-42
Flash point	ASTM D92	°C	100
Sulphated ash content	ASTM D874	%	0

DYADE
LUBRICANTS

Product information

People buy this product because they want a semi-synthetic 2-stroke outboard engine oil with NMMA TC-W3 specification.

CATEGORY

- Outboard
- Engine Oil

BASE OIL

- Semi-Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

