
HYDRAU-PLUS BIO UVS 22

BIODEGRADABLE HYDRAULIC OILS

326100201



BIODEGRADABLE HYDRAULIC FLUID FROM RENEWABLE SOURCES

This line of hydraulic oils consists of synthetic esters derived from unsaturated vegetable sources that are environmentally friendly. The oils are composed of high viscosity base oils, which contribute to their low pour points. Additionally, they are formulated with an additive package that provides excellent oxidation stability, anticorrosion, and anti-wear properties. These oils also have minimal impact on aquatic and marine ecosystems. These hydraulic oils are an ideal replacement for traditional mineral oils in both stationary and mobile hydraulic systems, particularly in areas where spills or leaks are more likely to occur. Such systems are typically encountered in offshore settings, as well as marine environments, including subsea installations, harbor cranes, and life-saving equipment.

PROPERTY	METHOD	VALUE	
Density @ 20 °C, kg/dm³	ISO 3675	0.91	
Viscosity @ 40 °C, mm²/s	ISO 3104	22	
Viscosity @ 100 °C, mm²/s	ISO 3104	4.5	
Viscosity index	ASTM D2270	150	
Pour point, °C	ASTM D97	<-44	
Flash point C.O.C, °C	ASTM D93	>200	
Dry TOST, hours	ASTM D943	>600	



CATEGORY

Hydraulic Fluids

BENEFITS

- Very high viscosity index
- High shear stability
- Good lubricating properties
- Good oxidation stability resulting in a very long lifetime and reduced cost
- Excellent seal compatibility
- Miscible with conventional mineral oils
- European Ecolabel reg. number NL/27/002
- Swedish Standard SS 15 54 34 SP listed CEC L-33-A-93 biodegradability of >90 %





