GEAR-PLUS ECO EST MAX 320

BIODEGRADABLE GEAR OILS

326300101



SATURATED ESTER BASED BIODEGRADABLE LUBRICANT FOR GEARBOXES IN WINDMILLS

This premium synthetic biodegradable gear oil is designed to provide excellent anti-wear and extreme pressure (AW/EP) protection, as well as corrosion control, even under the most challenging conditions. Specifically formulated for wind turbine gearbox lubrication, this product ensures optimal performance and extended service life. It maintains a high viscosity index that minimizes changes in viscosity at high temperatures while providing good low-temperature fluidity for cold-weather operation. Additionally, it exhibits exceptional resistance to micropitting and high scuffing loads. Being composed of a saturated ester base, this gear oil is biodegradable and environmentally friendly, making it a good choice for sensitive areas, such as those in open sea environments.

| PROPERTY | METHOD | VALUE | |
|-----------------------------------|-------------|-------|--|
| Density @ 15 °C, kg/dm³ | | 1.01 | |
| Viscosity @ 40 °C, mm²/s | | 320 | |
| Viscosity @ 100 °C, mm²/s | | 37-38 | |
| Viscosity index | | 145 | |
| Pour point, °C | | -33 | |
| Flash point, °C | | 270 | |
| Rust Test | ISO 7120 | pass | |
| Rust Test B (sea water) | ISO 7120 | pass | |
| FZG micropitting FVA 54/7 at 90°C | FVA 54/7 | >10 | |
| FZG scuffing test DIN ISO 14635-1 | ISO 14635-1 | >12 | |



CATEGORY

Gear Oils

BENEFITS

- Protects against micropitting and scuffing of gear teeth and provides extended bearing life under extreme conditions
- Withstands oxidative and thermal breakdown at elevated temperatures to increase time between drain intervals, saving time and labor
- High quality synthetic base stocks with high VI ensure good lubricant film thickness over a broad temperature range
- Low temperature fluidity ensures smooth cold temperature starts
- Resists rust and corrosion
- Excellent air release properties
- Excellent compatibility with seals and coatings



