

GAS-PLUS DI-EST 32

GAS COMPRESSOR OILS

326800101



SYNTHETIC DI-ESTER BASED COMPRESSOR FLUIDS FOR GAS COMPRESSOR APPLICATIONS

This particular product is comprised of high-quality synthetic ester base fluids and specially formulated additive systems. It has a proven track record for providing long-lasting lubrication in screw, rotary vane, or reciprocating (piston type) compressors. This product has been shown to be highly effective in compressing a wide range of gases, including Air, Butadiene, Carbon Dioxide (dry), Carbon Monoxide, Ethylene, Furnace (crack) Gas, Helium, Hydrogen, Hydrogen Sulphide (dry), Natural Gas, Methane, Nitrogen, Propane, Synthesis Gas, Sulphur Hexafluoride, and more. It has a nominal operating range of -15°C to 230°C, and provides exceptional protection to compressors operating in extreme conditions. This includes high loads and temperatures, compressing reactive and dirty gases, intermittent operation, as well as operating in warm or cold climates, and even in mobile applications.

PROPERTY

PROPERTY	METHOD	VALUE
ISO Viscosity Grade	ASTM D2422	32
Viscosity @ 40 °C, mm ² /s	ASTM D445	5.4
Viscosity @ 100 °C, mm ² /s	ASTM D445	33
Viscosity index	ASTM D2422	96
Pour point, °C	ASTM D97	-54
Flash point C.O.C, °C	ASTM D92	250
Demulsibility	ASTM D1401	excellent
Evaporation, %	ASTM D972	<1
Copper Corrosion	ASTM D130	1a
Density @ 15 °C, kg/dm ³	ASTM D1298	0.95

CATEGORY

- Compressor- and Vacuum pump Fluids

BENEFITS

- These products have a multitude of advantages over mineral and other synthetic oils: Reduced compressor maintenance with very long drain intervals. Up to 8 times the service life of mineral oils
- Low friction properties and resistance to viscosity increase from oxidation. This helps to improve operating efficiency and saves money on electrical energy consumption
- Excellent foam control, reducing heat, oxidation and wear. High contact regions are protected against wear for increased compressor life and efficiency
- Enhanced water separation. Water from condensation can cause unwanted oil/water emulsions, environmental discharge hazards and rust. It resists acid formation, readily separates from water and is anti-rust fortified. Water can be easily drained off for simplified environmental discharge and increased oil life
- Increased resistance to varnish, carbon and acid formation. Providing better protection and longer service life than petroleum oils, especially during hot operating conditions
- Low volatility, resulting in lower evaporation losses and fewer problems with the oil getting into air tools, instruments or even the production process. It also means there is less oil to remove in the air/oil separators and fewer air filter changes
- Fire and explosion possibilities are greatly reduced due to the low carbon forming tendencies and due to the relatively high flash, fire and auto ignition points. Operating temperature reduction. It cools and removes heat more efficiently. These benefits mean for the user of this product: higher reliability and lower operational costs. The reliability is also supported by our own oil analysis program.

All data on this technical data sheet is indicative only

202312V01



DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM

DYADE MAINTAIN THE THINGS WE VALUE