

GAS-PLUS PAG 220

GAS COMPRESSOR OILS

326801101



POLYALKYLENE GLYCOL (PAG) GAS COMPRESSOR LUBRICANT

The synthetic lubricants in question are made by blending high-quality polyalkylene glycol (PAG) base oils with specially formulated additive systems. They are intended for use in compressors, vacuum pumps, and other applications where the unique properties of these fluids are necessary. When used in hydrocarbon gas compression, these oils preserve their unique viscosity-temperature relationships by resisting thinning out from hydrocarbon dilution. With proper operating conditions, this product can provide a compressor service life of 8,000 to 10,000 hours. These products are applicable for use in a variety of compressors and vacuum pumps, including Rotary Screw Compressors, Rotary Vane Compressors, Centrifugal Compressors, and Reciprocating Compressors.

CATEGORY

- Compressor- and Vacuum pump Fluids

BENEFITS

- Gastop PG Series offers: Excellent oxidative and thermal stability
- Protection against hydrocarbon washout/dilution
- Extended drain life
- Reduced sludge and deposit formation

PROPERTY	METHOD	VALUE
ISO Viscosity Grade	ASTM D2422	220
Viscosity index	ASTM D2270	230
Viscosity @ 40 °C, mm ² /s	ASTM D445	220
Viscosity @ 100 °C, mm ² /s	ASTM D445	39
Flash point, °C	ASTM D92	230
Pour point, °C	ASTM D97	-32
Copper corrosion 24h @ 100 °C	ASTM D130	1b
Density @ 15 °C, kg/dm ³	ASTM D1298	1.07

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM