

MOULD-PLUS WSCA

MOULD RELEASE FLUIDS

327300501



CONCENTRATED WATER SOLUBLE CONCRETE RELEASE AGENT

This concrete release agent is specifically designed to optimize the complete release of concrete forms, particularly those made of iron and wood. This product is water-soluble and provides excellent results even at lower temperatures. It can also be used to protect molds from rust by impregnating them with the concentrate, ensuring they can be kept and stored in perfect condition. To use this product, dilute it with water at a ratio of 1:4 or 1:5. Ensure that the water hardness is not more than 400. You can apply the diluted product using a brush, roller, or spray. To create the emulsion, add the product to water and shake it gently, as it dissolves easily. Avoid adding water to the product.

CATEGORY

- Industry Specific

BENEFITS

- Operator friendly
- No dust on pieces
- Longer mould life
- Good finishing and fast release
- High efficiency
- Economic in use

PROPERTY

PROPERTY	METHOD	VALUE
Appearance		Oily liquid
Colour		Amber
Emulsion		White milky
Density @ 20 °C, kg/dm ³		0.83

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM