

# MOULD-PLUS CRA

MOULD RELEASE FLUIDS

327300601



## SOLUBLE CONCRETE RELEASE AGENT

This product is designed to facilitate the complete release of concrete forms, particularly when using molds made of iron or wood. Additionally, it can be used to provide protection against oxidation for molds when needed. To ensure an easy and complete release of concrete form when using iron and wood molds, this product is formulated for that purpose. It can also serve as a mold protector against oxidation if needed. To use, dilute the product with water up to 400 ppm hardness at a ratio of 1 part product to 9 parts water. It can be applied with a brush, roller, or spray. To prepare the emulsion, add the product to water, not the reverse, and shake lightly as it dissolves easily. However, if using the product to prevent mold oxidation, do not mix it with water.

## CATEGORY

- Industry Specific

## BENEFITS

- Good release properties
- Operator friendly
- No dust on pieces
- High efficiency
- Economic
- Longer mold life

PROPERTY	METHOD	VALUE
Appearance		Oily
Colour		Amber
Emulsion color		White milky
Viscosity @ 40 °C, mm <sup>2</sup> /s		110

All data on this technical data sheet is indicative only

202312V01



DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM

DYADE MAINTAIN THE THINGS WE VALUE