

SPINDLE-PLUS

III

SPINDLE OILS

327500301

DYADE

LUBRICANTS



SPINDLE OIL

The purpose of this product is to lubricate high-speed machine components that operate under medium load and temperature conditions. It is a refined mineral oil with a lightweight consistency. These oils do not contain any ash and are formulated with rust and corrosion inhibitors that provide exceptional oxidation resistance and thermal stability, even at high temperatures. For lubricating spindles, rolling bearings, automatic clutch bearings, and conveyor bearings, these fluids are highly recommended. They can be applied using various methods, including spraying, centralized systems, dipping, and dripping. These fluids are certified to meet ISO 6743/2 standards and are classified as ISO-L-FC.

CATEGORY

- Industry Specific

BENEFITS

- Zinc free (ashless technology)
- Excellent protection against rust and corrosion
- Reducing wear
- Increased heat and machine management
- Longer spindle bearing life
- Increased productivity

PROPERTY	METHOD	VALUE
Appearance		Oily liquid
Colour		Yellow
Viscosity @ 40 °C, mm ² /s		10
Grade, ISO 3448		10
Flash point C.O.C, °C		140
Pour point, °C		-14

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM